

Activated carbons for water treatments								
Type	Diameter (mm) Mesh	I. D. (mg/g) min	Ash (% max)	Apparent Density (g/l)	M. B. (mg/g min)	Moisture (% max)	Hardness (% min)	Ph
ZJ-15	∅ 1.5	800-1000	7---15	450-600		5	95	8---11
ZJ-30	∅ 3.0	800-1000	7---15	450-600		5	95	8---11
ZJ-40	∅ 4.0	800-1000	7---15	450-600		5	95	8---11
PJ-8*30	8*30	500-1050	7---20	400-600	100-200	5	90 or 95	8---11
PJ-12*40	12*40	500-1050	7---20	400-600	100-200	5	90 or 95	
PJ-20*50	20*50	500-1050	7---20	400-600				
FJ 100	100	500-1000	10-up		100-200	5		
FJ 200	200	500-1000	10-up		100-200	5		
FJ 325	375	500-1000	10-up		100-200	5		
PS:Carbons can be manufactured and supplied according to customer' s demands								

## Packaging

Standard packaging is designed primarily to prevent deterioration of accurately graded granules and preclude the adsorption of moisture or atmospheric contaminants. Other packaging criteria can be accommodated on request.

Bulk Bag

Sacks Net. 500 Kg Net. 25 Kg

### Warranty Disclaimer

Please confirm the specification of any particular grade with your representative prior to purchase. The user is responsible for ensuring that the product is correctly specified prior to purchase and Baiyun makes no express warranty as to suitability for specific application

## **BAIYUN** **Activated carbon solutions**

- Email: baiyun.sarah@outlook.com
- Tel:+86 15617916052
- whatsapp: +86 15617916052
- Skype: +86 15617916052

Factory Add(Ningxia):

Longhu Economic Development Zone, Dawukou District, Shizuishan City, Ningxia Hui Autonomous Region